



$\alpha$  - угол контакта.

| Основные размеры подшипников |               | Обозначение | Размеры, мм       | Масса, кг |
|------------------------------|---------------|-------------|-------------------|-----------|
| ГОСТ 26200-89                | Стандарт De r |             |                   |           |
| Серия ширин                  |               | 0           | , серия диаметров | 2         |
| <a href="#">26200K</a>       | -             | 10          | 30                | 9         |
| <a href="#">26201K</a>       | -             | 12          | 32                | 10        |
| <a href="#">26202K</a>       | -             | 15          | 35                | 11        |

|                        |   |    |     |    |
|------------------------|---|----|-----|----|
| <a href="#">26203K</a> | - | 17 | 40  | 12 |
| <a href="#">26204K</a> | - | 20 | 47  | 14 |
| <a href="#">26205K</a> | - | 25 | 52  | 15 |
| <a href="#">26206K</a> | - | 30 | 62  | 16 |
| <a href="#">26207K</a> | - | 37 | 72  | 17 |
| <a href="#">26208K</a> | - | 40 | 80  | 18 |
| <a href="#">26209K</a> | - | 45 | 85  | 19 |
| <a href="#">26210K</a> | - | 50 | 90  | 20 |
| <a href="#">26211K</a> | - | 55 | 100 | 21 |
| <a href="#">26212K</a> | - | 60 | 110 | 22 |
| <a href="#">26213K</a> | - | 65 | 120 | 23 |
| <a href="#">26214K</a> | - | 70 | 125 | 24 |

|                        |   |     |     |    |
|------------------------|---|-----|-----|----|
| <a href="#">26215K</a> | - | 75  | 130 | 25 |
| <a href="#">26216K</a> | - | 80  | 140 | 26 |
| <a href="#">26217K</a> | - | 85  | 150 | 28 |
| <a href="#">26218K</a> | - | 90  | 160 | 30 |
| <a href="#">26219K</a> | - | 95  | 170 | 32 |
| <a href="#">26220K</a> | - | 100 | 180 | 34 |
| <a href="#">26222K</a> | - | 110 | 200 | 38 |
| <a href="#">26224K</a> | - | 120 | 215 | 40 |
| <a href="#">26226K</a> | - | 130 | 230 | 40 |
| <a href="#">26228K</a> | - | 140 | 250 | 42 |
| <a href="#">26230K</a> | - | 150 | 270 | 45 |

| Серия ширин            | 0 | , серия диаметров | 3   |    |
|------------------------|---|-------------------|-----|----|
| <a href="#">26300K</a> | - | 10                | 35  | 11 |
| <a href="#">26301K</a> | - | 12                | 37  | 12 |
| <a href="#">26302K</a> | - | 15                | 42  | 13 |
| <a href="#">26303K</a> | - | 17                | 47  | 14 |
| <a href="#">26304K</a> | - | 20                | 52  | 15 |
| <a href="#">26305K</a> | - | 25                | 62  | 17 |
| <a href="#">26306K</a> | - | 30                | 72  | 19 |
| <a href="#">26307K</a> | - | 35                | 80  | 21 |
| <a href="#">26308K</a> | - | 40                | 90  | 23 |
| <a href="#">26309K</a> | - | 45                | 100 | 25 |
| <a href="#">26310K</a> | - | 50                | 110 | 27 |

|                        |   |     |     |    |
|------------------------|---|-----|-----|----|
| <a href="#">26311K</a> | - | 55  | 120 | 29 |
| <a href="#">26312K</a> | - | 60  | 130 | 31 |
| <a href="#">26313K</a> | - | 65  | 140 | 33 |
| <a href="#">26314K</a> | - | 70  | 150 | 35 |
| <a href="#">26315K</a> | - | 75  | 160 | 37 |
| <a href="#">26316K</a> | - | 80  | 170 | 39 |
| <a href="#">26317K</a> | - | 85  | 180 | 41 |
| <a href="#">26318K</a> | - | 90  | 190 | 43 |
| <a href="#">26320K</a> | - | 100 | 215 | 47 |
| <a href="#">26322K</a> | - | 110 | 240 | 50 |
| <a href="#">26324K</a> | - | 120 | 260 | 55 |
| <a href="#">26326K</a> | - | 130 | 280 | 58 |

|                        |   |     |     |    |
|------------------------|---|-----|-----|----|
| <a href="#">26328K</a> | - | 140 | 300 | 62 |
| <a href="#">26330K</a> | - | 150 | 320 | 65 |
| <a href="#">26332K</a> | - | 160 | 340 | 68 |
| <a href="#">26334K</a> | - | 170 | 360 | 72 |

Масса подшипников рассчитана для плотности стали 7,85 кг/дм<sup>3</sup>.